

TECHNICAL DATA SHEET

Spectro Performance Oils PLATINUM SYN-SNO POWERVALVE



- ▶ Meets all known snowmobile manufacturers' warranty requirements & recommendations.
- ▶ Exceeds JASO FD, ISO-L-EGD + and A.P.I. TC test requirements.
- ▶ Unsurpassed in cleanliness and low smoke emissions.
- ▶ Highest lubricity and torque indexes.
- ▶ For use in all two-cycle Arctic-Cat, Polaris, Yamaha and Ski-Doo snowmobile engines without restriction.

DESCRIPTION

Spectro Platinum Syn-Sno Powervalve formula snowmobile oil is the ultimate two-cycle lubricant formulated specifically for use in modern two-cycle snowmobiles equipped with exhaust power valves. A full synthetic formulation with breakthrough additive technology (polybutenes, borated polyisobutanyl succinic anhydride nitrogen functionalized dispersant, mixed calcium alkylaryl detergent) combines to provide virtually smokeless operation and residue-free engine cleanliness. No oil anywhere burns cleaner than this JASO FD and ISO-EGD PLUS oil. Tisi engine tested.

APPLICATION

Spectro Platinum Syn-Sno is formulated specifically for use in all modern, two-cycle snowmobiles in weather down to -42 degrees centigrade.

FOR RACING USE

Spectro Platinum Syn-Sno can be mixed at the manufacturer's recommended ratio or used in injector systems. Otherwise, mix thoroughly at a 50:1 fuel to oil ratio (2.5 ounces per gallon, 12.5 oz to five (5) gallons). No special steps need to be taken when switching to Spectro Platinum Syn-Sno Powervalve Formula.

TYPICAL INSPECTIONS

Kinematic Gravity @ 60/60°F	0.849
Kinematic Viscosity @ 100°C cST	7
Kinematic Viscosity @ 40°C cST	36.65
Flash Point, °C	94
Pourpoint, °C	-42
Sulfurated Ash, Wt%	0.09
Brookfield Viscosity @ -25°C cP	2,240
Brookfield Viscosity @ -40°C cP	41,600

CODE

R.SYNSNO
T.SYNSNO

DESCRIPTION

12/32 Ounce Bottles
4/1 Gallon Bottles

WEIGHT

25 lbs
33 lbs

CONTACT

Spectro Performance Oils

800-243-8645 | TheOilExperts@Spectro-Oils.com

993 Federal Road, Brookfield, CT 06804



Updated: Jan 2019