

Model 9902R

Model 9895R

## CAMSO

## Ice and Grass Drag

Ahead of the pack

Designed specifically for the intense acceleration of drag racing, where the first seconds of the race make the difference between winning and losing.

- Low-resistance 0.525" lugs require less fuel for optimal straight-line acceleration
- 13.5" width available for lightweight and maximum top speed
- Multiple lengths for a wide variety of race chassis

## CAMSO

## Asphalt Drag

Made for asphalt drag competitions

Engineered and built for the unique performance requirements of asphalt drag competitions, where traction and super-fast acceleration are the name of the game.

- Lightweight 10.625" width for maximum top speed
- Soft outer rubber provides traction on paved surfaces
- Multiple lengths for a wide variety of race chassis

MODEL	DIMENSIONS	LUG HEIGHT	WEIGHT	DRIVE PITCH	CLIP CONFIG.	MODEL	DIMENSIONS	LUG HEIGHT	WEIGHT	DRIVE PITCH	CLIP CONFIG.
9084R	13.5" x 144" (34 cm x 366 cm)	0.525" (13 mm)	35 lb. (15.75 kg)	2.52" (64 mm)	Full	9895R	10.625" x 121" (27 cm x 307 cm)	0.625" (16 mm)	33 lb. (15 kg)	2.52" (64 mm)	No windows / clips
9359R	14" x 144" (36 cm x 366 cm)	1" (25 mm)	38 lb. (17.25 kg)	2.52" (64 mm)	Full	9896R	10.625" x 128" (27 cm x 325 cm)	0.625" (16 mm)	35 lb. (15.75 kg)	2.52" (64 mm)	No windows / clips
9811R	15" x 121" (38 cm x 307 cm)	0.525" (13 mm)	33 lb. (15 kg)	2.52" (64 mm)	Full	9897R	10.625" x 136" (27 cm x 345 cm)	0.625" (16 mm)	37 lb. (16.75 kg)	2.52" (64 mm)	No windows / clips
9902R	13.5" x 128" (34 cm x 325 cm)	0.525" (13 mm)	33 lb. (15 kg)	2.52" (64 mm)	Full						
9929R	13.5" x 136" (34 cm x 345 cm)	0.525" (13 mm)	31 lb. (14 kg)	2.52" (64 mm)	No windows / clips						
9976R	13.5" x 144" (34 cm x 366 cm)	0.525" (13 mm)	33 lb. (15 kg)	2.52" (64 mm)	No windows / clips						