

SPECTRO LUBRICANT TECHNICAL DATA

Spectro Sno Injector



Description

Spectro Sno is a superior petroleum snowmobile lubricant developed to excel over the baseline OEM oils. Spectro Sno offers cleaner operation, free from plug fouling. Constant pumping and flow are assured even at extreme sub-zero temperatures. A special additive system protects all internal engine parts during off-season storage.

Application

Spectro Sno is specifically formulated to be used in all modern snowmobiles with auto-injection systems or as a pre-mix. A ratio of 32:1 to 50:1 may be used for pre-mix use.

Meets or exceeds all manufacturers' warranty requirements.

Typical Inspections

Kinematic Viscosity @ 100° C cST	9.1
Kinematic Viscosity @ 40° C cST	70
Flash Point, °C	216
Pourpoint, °C	-50
Color	Red

Code	Description	Weight
R.SNO	12/1 Qt. Bottles	25 Lbs.
T.SNO	4/1 Gal. Bottles	33 Lbs.
Z.SNO	1/55 Gal. Drum	450 Lbs.

- MINIMIZES SPARK PLUG FOULING.
- CONTAINS LOW SMOKE ADDITIVES TO REDUCE SMOKING SIGNIFICANTLY.
- REDUCES EXHAUST OUTLET DEPOSITS.
- GUARDS AGAINST PISTON SEIZURE.
- EXCEPTIONAL OFF-SEASON PROTECTION OF INTERNAL PARTS.
- API TC & JASO FB QUALITY.
- COMPLETELY MISCIBLE WITH ALL OEM OILS.