



PREMIUM

HIGH PERFORMANCE 4-STROKE ENGINE OIL

DESCRIPTION:

Mineral based 4-stroke engine oil designed to ensure optimum protection, peak performance and positive clutch feel. Provides excellent film thickness and viscosity stability across all operating temperatures. Advanced, proprietary additive system keeps your engine running clean, trouble-free and extends the life of the machine. Exceeds the requirements of API SL / JASO MA2.

FEATURES & BENEFITS:

- Superior protection at any temperature
- Excellent clutch feel and clutch protection
- Shear stable formula maintains oil viscosity and film thickness
- Optimizes cleanliness while controlling oxidation and wear
- Exceeds API SL and JASO MA2 specifications

APPLICATIONS:

For all air and water-cooled 4-stroke gasoline engines.

TECHNICAL DATA

| SPECIFICATION | TEST METHOD | 5W30 | 10W30 | 10W40 | 20W50 |
|-------------------------|-------------|-------|-------|-------|-------|
| APPEARANCE | VISUAL | Amber | Amber | Amber | Amber |
| VISCOSITY @ 40°C (cSt) | D445 | 60.7 | 78.0 | 95.4 | 167.7 |
| VISCOSITY @ 100°C (cSt) | D445 | 10.2 | 11.5 | 14.8 | 20.3 |
| VISCOSITY INDEX | D2270 | 157 | 139 | 162 | 141 |
| FLASH POINT (°C) | D92 | 202 | 205 | 206 | 208 |
| POUR POINT (°C) | D97 | -39 | -39 | -36 | -30 |
| DENSITY @ 15 °C (g/ml) | D4052 | 0.863 | 0.869 | 0.866 | 0.871 |

EXPERIENCE THE DIFFERENCE

Made In The USA